

Material Type: FABRIC

Type of Testing: TENSILE

EDGECOMB TEST FIXTURE



Model No. ASTM.D0751.60 ASTM.D6479.10 Specimen Size or Difference Between Fixtures

2" wide and 6" long 2" wide, 12" long, 0.125" thick Construction

Stainless steel Stainless steel **Temperature**

-240 to 600°F (-152 to 318°C) -240 to 600°F (-152 to 318°C)

Fixture: Mounting Top: 12mm male clevis

Bottom: grip (grip not included)

Capacity 500 lbs (2.2 kN)

Weight 3 lbs Dimensions 2" x 1" x 4.5

Standard Manufactured in compliance with ASTM D751 and D6479

QUOTE

Model No. ASTM.D6479.10 - Edgecomb Test Fixture for Fabrics

Fixture is equipped with twelve equally spaced 1mm diameter pins that are 8mm in length. Fixture has corresponding 1.5mm diameter holes with a stop located 5mm from the center of the holes. Supplied with custom 12mm male clevis for mounting to the cross head. Does not include lower grip to hold fabric specimen. Fixture is constructed of stainless steel and is manufactured in compliance with ASTM D6479.

ACCESSORIES

Model No. GRIP.10100.201- (1) 200lbs Screw Action Grip with 3" x 1" Wide Grip Faces Grip comes with 1/2"-20 threaded stud for mounting purposes.

SPARE PARTS

Model No. SPA.D6479.1001 - Set of (12) Replacement Needles for MTT Model No. ASTM.D6479.10

COMMON SIZE ADAPTERS

Upper Mounting: 12mm Male Clevis

Model No. M12M01 - 12mm Male Clevis to 1/2" Male Clevis Model No. M12M02 - 12mm Male Clevis to 5/8" Male Clevis Model No. M12M03 - 12mm Male Clevis to 1.25" Male Clevis Model No. M12S48 - 12mm Male Clevis to 1.5"-12 Threaded Stud Model No. M12S42 - 12mm Male Clevis to 1.25"-12 Threaded Stud Model No. M12S36 - 12mm Male Clevis to 1"-14 Threaded Stud