



Standards:
ASTM F2704 - 10

Material Type:
FITTING

Type of Testing:
TENSILE

MODEL NO. ASTM.F2704.20

EXTERNAL FITTING PULL OUT STRENGTH TEST FIXTURE



Model No.
ASTM.F2704.20

Specimen Size or Difference Between Fixtures
10" by 10" square

Construction
Aluminum

Temperature
Ambient

Fixture:	Mounting	Upper: grip (grip sold separately) Lower: 1"-14 threaded coupling
	Capacity	
	Weight	
	Dimensions	
	Standard	Manufactured in compliance with ASTM F2704

QUOTE

Model No. ASTM.F2704.20 - Custom External Fitting Pull Out Strength Test Fixture

The fixture clamps the 10" square suit material specimen with an external fitting over a 6" diameter hole between two clamping plates. The clamping plates are hinged and held together with a clamp. The clamping plates are supported 8" above the base plate, which is supplied with a 1" -14 threaded coupling. The fixture is also supplied with a 10" square specimen cutting template. Does not include upper grip. Constructed of aluminum with a protective finish in accordance with ASTM D2704.

ACCESSORIES

Model No. GRIP.20100.101 - (1) 5,000 Pound Wedge Action Grip with Faces for 0-1" Wide

SPARE PARTS

Model No. SPA.F2704.2001 - Replacement 10" Square Specimen Template

COMMON SIZE ADAPTERS

Lower Mounting: 1"-14 Female Coupling

Model No. M03S36 - 1.25" Male Clevis to 1"-14 Threaded Stud

Model No. S42S36 - 1.25"-12 to 1"-14 Threaded Step Stud

Model No. S48S36 - 1.5"-12 to 1"-14 Threaded Step Stud

Model No. S60S36 - 2"-12 to 1"-14 Threaded Step Stud

Model No. LN36 - 1"-14 Threaded Locking Nut with Knurled OD